



# DF-81 TDE

HIGH PERFORMANCE  
DOUBLE COATED TAPE

REQUEST A  
SAMPLE TODAY!

## Double Coated Tape

- High performance adhesive system
- Reliable bond with clean removability
- Extended liner with true dry edge (TDE)
- Excellent for non-refrigerated marking labels
- Available in full coat/edge to edge construction

## Technical Info

- 42# printed/unprinted SCK paper release liner
- Rubber-based hot melt adhesive
- 90 oz./in liner side adhesion
- 90 oz./in exposed side adhesion
- 0.48 mil (12u) clear polyester carrier

## Applications

- Shelf talkers
- Marking labels

Part Number	Item Description	Adhesive Technology	Application
DF-81 TDE	Double coated tape	Permanent/Removable	Marking labels



Scan the code to request a sample or speak with our knowledgeable sales team.

CONTACT OUR TAPE  
EXPERTS TODAY TO DISCUSS  
YOUR APPLICATION!



## DF-81 TDE Technical Data Sheet

## Double Coated Shelf Talker Tape

High Performance Double Coated Tape for mounting Shelf Talker Labels

### Product Features

- Extended Liner with True Dry Edge (TDE)
- Performance Adhesive for strong bond and clean removal
- Excellent for non-refrigerated marking labels
- Also available in full coat/edge to edge construction

	Overall Liner Widths Available	Adhesive Width Liner Side	Adhesive Width Exposed Side
<b>Release Liner</b>	1/2" (12mm)	3/16" (5mm)	5/16" (8mm)
<b>42# Printed/Unprinted SCK Paper</b>	3/4" (19mm)	7/16" (11mm)	9/16" (14mm)
<b>Adhesive</b>	7/8" (22mm)	9/16" (14mm)	5/8" (16mm)
<b>Rubber Based Hot Melt</b>	<b>Available Widths</b>	<b>Adhesive Thickness</b>	<b>Adhesive Thickness</b>
<b>Liner Side Adhesion *</b>	1/2" (12mm)	1.3 mils	1.1 mils
<b>90 oz./in</b>	3/4" (19mm)	1.3 mils	1.1 mils
<b>Exposed Side Adhesion *</b>	7/8" (22mm)	1.3 mils	1.1 mils
<b>90 oz./in</b>	<b>Diameter</b>	<b>Weight</b>	<b>Weight per Case</b>
<b>Carrier</b>	1/2" - 16.75"	3.5#/roll (1.58Kg)	36# (16.33Kg)
<b>0.48 mil (12u) Clear Polyester</b>	3/4" - 16.75"	6.0#/roll (2.72Kg)	44# (19.96Kg)
	7/8" - 16.75"	10#/roll (4.53Kg)	51# (23.13Kg)
	<b>Flat Rolls Per Case</b>	<b>Spools Per Case</b>	<b>Cases per Skid (Cases / Spools)</b>
	1/2" x 3,500' (1,067m) - 12	N/A	24
	3/4" x 3,500' (1,067m) - 8	N/A	24
	7/8" x 3,500' (1,067m) - 6	N/A	24

\* Above Reflect Typical Values

### Notes:

- Adhesives Are Compliant With FDA Regulations For Indirect Food Contact - CFR 175.105
- Recommended Storage Conditions: 60-80 °F at 40-60% RH
- Ideal product application temperature range is 70°F to 100°F (21°C to 38°C). Initial application to surfaces at temperatures below 50°F (10°C) is not recommended

Fitness for Use in any end application is the sole responsibility of the user. Infinity Tapes makes no additional claims or warranties for suitability or fitness for use beyond those stated in our standard Terms & Conditions.