

DF25TDE

UTILITY-GRADE DOUBLE COATED TAPE

REQUEST A
SAMPLE TODAY!

Double Coated Tape

- Utility-grade general purpose adhesive system
- Extended liner with true dry edge (TDE)
- Available in full coat/edge to edge construction
- Clean removal from most surfaces
- Excellent for non-refrigerated marking labels

Technical Info

- 42# printed/unprinted SCK paper release liner
- Rubber-based hot melt
- 100 oz./in liner side adhesion
- 90 oz./in exposed side adhesion
- 0.48 mil (12u) clear polyester carrier

Applications

- Mounting shelf talker labels

Part Number	Item Description	Adhesive Technology	Application
DF25TDE	Double coated shelf talker tape	Permanent/Removable	Shelf talker labeling



Scan the code to request a sample or speak with our knowledgeable sales team.

CONTACT OUR TAPE EXPERTS TODAY TO DISCUSS YOUR APPLICATION!



DF25 TDE Technical Data Sheet

Double Coated Shelf Talker Tape

Utility Grade Double Coated Tape for mounting Shelf Talker Labels

Product Features

- Extended Liner with True Dry Edge (TDE)
- Clean removal from most surfaces
- Excellent for non-refrigerated marking labels
- Also available in full coat/edge to edge construction

	Overall Liner Widths Available	Adhesive Width Liner Side	Adhesive Width Exposed Side
Release Liner	1/2" (12mm)	3/16" (5mm)	5/16" (8mm)
42# Printed/Unprinted SCK Paper	3/4" (19mm)	7/16" (11mm)	9/16" (14mm)
Adhesive	7/8" (22mm)	9/16" (14mm)	5/8" (16mm)
Rubber Based Hot Melt	Available Widths	Adhesive Thickness	Adhesive Thickness
Liner Side Adhesion *	1/2" (12mm)	1.3 mils	1.1 mils
100 oz./in	3/4" (19mm)	1.3 mils	1.1 mils
Exposed Side Adhesion *	7/8" (22mm)	1.3 mils	1.1 mils
90 oz./in	Diameter	Weight	Weight per Case
Carrier	1/2" - 16.75"	3.5#/roll (1.0Kg)	37# (16Kg)
0.48 mil (12u) Clear Polyester	3/4" - 16.75"	6.0#/roll (2.0Kg)	47# (21Kg)
	7/8" - 16.75"	10#/roll (4.0Kg)	52# (23Kg)
	Flat Rolls Per Case	Spools Per Case	Cases per Skid (Cases / Spools)
	1/2" x 3,500' (1,067m) - 12	N/A	24
	3/4" x 3,500' (1,067m) - 8	N/A	24
	1" x 3,500' (1,067m) - 7	N/A	24

* Above Reflect Typical Values

Notes:

- Adhesives Are Compliant With FDA Regulations For Indirect Food Contact - CFR 175.105
- Recommended Storage Conditions: 60-80 °F at 40-60% RH
- Ideal product application temperature range is 70°F to 100°F (21°C to 38°C). Initial application to surfaces at temperatures below 50°F (10°C) is not recommended

Fitness for Use in any end application is the sole responsibility of the user. Infinity Tapes makes no additional claims or warranties for suitability or fitness for use beyond those stated in our standard Terms & Conditions.