



DFBXTDE

DOUBLE COATED
PERMANENT TAPE

REQUEST A
SAMPLE TODAY!

Double Coated Tape

- High tack, aggressive bonding adhesive system
- Superior bonding in a variety of extreme conditions and environments
- Standard dry edge (TDE) construction

Technical Info

- 53# printed red SCK paper release liner
- Rubber-based hot melt adhesive
- 202 oz./in liner side adhesion
- 116 oz./in exposed side adhesion
- 0.48 mil (12u) clear polyester carrier

Applications

- Cardboard boxes
- Paper mailers

Part Number	Item Description	Adhesive Technology	Application
DFBXTDE	Double coated permanent tape	Permanent	Cardboard Boxes & Mailers



Scan the code to request a sample or speak with our knowledgeable sales team.

CONTACT OUR TAPE
EXPERTS TODAY TO DISCUSS
YOUR APPLICATION!



DFBXTDE Technical Data Sheet

Double Coated Tape

Double Coated Permanent Tape with Polyester Carrier and Paper Release Liner Designed for Corrugated Box Enclosures.

Product Features

- An Aggressive Adhesive System to Permanently Seal Cardboard Boxes and Paper Mailers with Superior Bonding Properties to Hold the Box Closed Under a Variety of Extreme Conditions.
- Standard Construction is TDE (True Dry Edge)

	Overall Liner Widths Available	Adhesive Width Liner Side	Adhesive Width Exposed Side
Release Liner	1.25" (32mm)	3/4" (19mm)	1.063" (27mm)
53# Printed Red SCK Paper	1.5" (38mm)	1.0" (25mm)	1.25" (32mm)
Adhesive	1.75" (44mm)	1.25" (32mm)	1.5" (38mm)
Rubber Based Hot Melt Adhesive	2" (51mm)	1.5" (38mm)	1.75" (44mm)
Liner Side Adhesion *	Available Widths	Adhesive Thickness	Adhesive Thickness
202 oz./in	1.25" (32mm)	3.5mils	2.5mils
Exposed Side Adhesion *	1.5" (38mm)	3.5mils	2.5mils
116 oz./in	1.75" (44mm)	3.5mils	2.5mils
Carrier	2" (51mm)	3.5mils	2.5mils

0.48 mil (12u) Clear Polyester

* Above Reflect Typical Values

Notes:

- Recommended Storage Conditions: 60-80 °F at 40-60% RH
- Ideal product application temperature range is 70°F to 100°F (21°C to 38°C). Initial application to surfaces at temperatures below 50°F (10°C) is not recommended

1" x 1.25" x 1.5"	1" with 3.5 mil adhesive thickness	1.25" with 2.5mil adhesive thickness
Flat Rolls Per Case	Spools Per Case	Cases per Skid (Cases / Spools)
1.25" x 1,620' (494m) - 5	N/A	24
1.5" x 1,620' (494mm) - 4	N/A	24
1.75" x 1,620' (494mm) - 3	N/A	24
2" x 1,620' (494mm) - 3	N/A	24

Fitness for Use in any end application is the sole responsibility of the user. Infinity Tapes makes no additional claims or warranties for suitability or fitness for use beyond those stated in our standard Terms & Conditions.