



HG53-2

TAMPER EVIDENT FILM & TAPE

REQUEST A
SAMPLE TODAY!

Tamper Evident Film & Tape

- Hidden graphic tamper evident film
- Excellent printing/converting properties
- Printable by digital or flexographic print methods
- Available in a variety of colors
- Customizable hidden graphic messaging

Technical Info

- 92ga or 142ga polyester film
- 42# SCK paper release liner
- Hot melt adhesive
- 1.1mil adhesive thickness
- Matte finish

Applications

- Plastic bags
- Corrugated boxes

Part Number	Item Description	Film Technology	Application
HG53-2	Tamper Evident Film & Tape	Polyester	Boxes & Bags



Scan the code to request a sample or speak with our knowledgeable sales team.

CONTACT OUR TAPE
EXPERTS TODAY TO DISCUSS
YOUR APPLICATION!



HG53-2 Technical Data Sheet

Tamper Evident Label Stock

HG53-2 is a Tamper Evident Film and Tape with a Special Matte Finish Containing a Hidden Graphic (HG) Message that Appears when the Product is Attempted to be Opened

Product Features

- Polyester Film Provides an Excellent Printing Surface
- Printable by Flexo or Digital Print Methods
- Hidden Graphic Message can be Customized to Any Message
- Available in a Variety of Colors

Tamper Evident Film Substrate			
92ga or 142ga Polyester Film	Room Temperature Tampering Evidence	Freon Tampering Evidence *	Heat Tampering Evidence *
Release Liner	Yes	Yes	Yes
42# SCK Paper	Widths		
Adhesive	Slit to Order in rolls to 4,500'		
Hot Melt	Fitness for Use in any end application is the sole responsibility of the user. Infinity Tapes makes no additional claims or warranties for suitability or fitness for use beyond those stated in our standard Terms & Conditions.		
Adhesive Thickness	1.1mils		

Storage and Handling Recommendations

1. Store in a cool dry area away from heat and sunlight
2. Apply minimum tension on the web, never stretch the bag film or the tape
3. Avoid sharp angles when removing the release liner
4. If high temperatures exist in the processing area (above 80 f) it is highly recommended that the product be "conditioned" in an air conditioned environment prior to use
5. Rotate stocks of tape
6. Recommended Storage Conditions: 60-80 °F at 40-60% RH
7. Ideal product application temperature range is 70°F to 100°F (21°C to 38°C). Initial application to surfaces at temperatures below 50°F (10°C) is not recommended

Notes:

* The substrate must be evaluated by the converter in their process to determine acceptable tamper evident characteristics. Base properties, chemical slip additives, inks, & adhesives can have an effect on tamper evident properties.