



HG63

TAMPER EVIDENT FILM

REQUEST A
SAMPLE TODAY!

Tamper Evident Tape

- Hidden graphic tamper evident film
- Reliable bonding and sealing
- Designed for heat sealing directly to HDPE and LDPE films
- Tape can be backside printed

Technical Info

- 2 mil (50 micron) HDPE film
- Slit to order

Applications

- HDPE bags
- LDPE bags

| Part Number | Item Description | Film Technology | Application |
|-------------|---------------------|-----------------|-------------|
| HG63 | Tamper Evident Film | HDPE Film | Film bags |



Scan the code to request a sample or speak with our knowledgeable sales team.

CONTACT OUR TAPE EXPERTS TODAY TO DISCUSS YOUR APPLICATION!



HG63 Technical Data Sheet

Tamper Evident Tape

HG63 is a Tamper Evident Film That Can Readily Heat Seal to Bag Film. A Hidden Graphic (HG) Message Appears When the Product is Attempted to be Opened.

Product Features

- Designed To Be Heat-Sealed Directly To HDPE & LDPE Films
- Back Surface of Tape Can Be Treated and Printed
- Recommended Storage Conditions: 60-80°F at 40-60% RH
- Ideal product application temperature range is 70°F to 100°F (21°C to 38°C). Initial application to surfaces at temperatures below 50°F (10°C) is not recommended

Tamper Evident Film Substrate

2 mil (50 micron) HDPE Film

Release Liner

N/A

Adhesive

None

Adhesive Thickness

N/A

Widths

Slit to Order

Notes:

The substrate must be evaluated by the converter in their process to determine acceptable tamper evident characteristics. Base properties, chemical slip additives, inks and adhesives can have adverse affects on the tamper evident properties

Fitness for Use in any end application is the sole responsibility of the user. Infinity Tapes makes no additional claims or warranties for suitability or fitness for use beyond those stated in our standard Terms & Conditions.