



HKC65

BAG CLOSURE SOLUTIONS

REQUEST A
SAMPLE TODAY!

Bag Closure Tape

- High performance bag closure tape
- Strong, aggressive, permanent bond
- Designed to tear films 3 mils (75 microns) thick and above
- Extended and dry edge technology

Technical Info

- 1.8 mil (45u) white polypropylene (BOPP) film
- Rubber-based permanent adhesive
- 123 oz./in liner side adhesion
- 71 oz./in exposed side adhesion
- 0.48 mil (12u) clear polyester carrier

Applications

- Plastic courier envelopes
- Plastic mailer envelopes

Part Number	Item Description	Adhesive Technology	Application
HKC65	Permanent Double Coated Tape	Permanent	Film Envelopes



Scan the code to request a sample or speak with our knowledgeable sales team.

CONTACT OUR TAPE EXPERTS TODAY TO DISCUSS YOUR APPLICATION!



Call 866-333-4886
for more information.

Infinity Tapes infinite possibilities

HK65 Technical Data Sheet

Double Coated Tape

High Performance Permanent Double Coated Tape with a polyester carrier with a White BOPP release liner

Product Features

- Excellent High Performance Bag Enclosure Tape
- Bonds Plastic Courier And Mailer Envelopes
- Designed To Tear Films 3Mils (75Microns) Thick And Above
- *Weights approximate due to variations in raw materials/packaging

	Overall Liner Widths Available	Adhesive Width Liner Side	Adhesive Width Exposed Side
Release Liner	1/2"(12mm)	1/4" (6mm)	1/2" (12mm)
1.8mil (45u) White Polypropylene (BOPP) Film	3/4" (19mm)	1/2" (12mm)	3/4" (19mm)
Adhesive	1" (25mm)	3/4" (19mm)	1" (25mm)
Rubber Based Adhesive	Available Widths	Adhesive Thickness	Adhesive Thickness
Liner Side Adhesion *	1/2"(12mm)	3.0mils	1.0mils
123 oz./in	3/4" (19mm)	3.0mils	1.0mils
Exposed Side Adhesion *	1" (25mm)	3.0mils	1.0mils
71 oz./in	Diameter	*Weight	Weight per Case
Carrier	1/2"(12mm) - 18" (457mm)	3#/roll (1.3 Kg)	48# (22 Kg)
0.48 mil (12u) Clear Polyester	3/4" (19mm) - 18" (457mm)	6#/roll (3.0 Kg)	48# (22 Kg)
	1" (25mm) - 18" (457mm)	8#/roll (4.0 Kg)	50# (23 Kg)
	Flat Rolls Per Case	Spools Per Case	Cases per Skid (Cases / Spools)
	1/2" x 3,000' (915m) - 12	1/2" x 21,000' (6,400m) - 1 *Weight 23#/Spool/Case	24 / 45
	3/4" x 3,000' (915m) - 8	3/4" x 15,000' (4,572m) - 1 *Weight 28#/Spool/Case	24 / 45
	1" x 3,000' (915m) - 6	1" x 12,000' (3,658m) - 1 *Weight 31#/Spool/Case	24 / 45

* Above Reflect Typical Values

Notes:

- Low Slip Or No Slip Films Are Highly Recommended
- Corona Treatment On Film Surfaces Improves Adhesion Properties
- Adhesives Are Compliant With FDA Regulations For Indirect Food Contact - CFR 175.105
- Recommended Storage Conditions: 60-80 ° F at 40-60% RH
- Ideal product application temperature range is 70°F to 100°F (21°C to 38°C). Initial application to surfaces at temperatures below 50°F (10°C) is not recommended

Fitness for Use in any end application is the sole responsibility of the user. Infinity Tapes makes no additional claims or warranties for suitability or fitness for use beyond those stated in our standard Terms & Conditions.