



HKC67

ENVELOPE CLOSURE SOLUTIONS

REQUEST A
SAMPLE TODAY!

Tamper Evident Tape

- General purpose bag closure tape
- Strong, aggressive, permanent bond
- Designed to tear films up to 3 mils (75 microns) thick
- Extended and dry edge technology

Technical Info

- 1.8 mil (45u) white polypropylene (BOPP) film
- Rubber-based permanent adhesive
- 92 oz./in liner side adhesion
- 71 oz./in exposed side adhesion
- 0.48 mil (12u) clear polyester carrier

Applications

- Plastic courier envelopes
- Plastic mailer envelopes

Part Number	Item Description	Adhesive Technology	Application
HKC67	Permanent Double Coated Tape	Permanent	Film Envelopes



Scan the code to request a sample or speak with our knowledgeable sales team.

CONTACT OUR TAPE EXPERTS TODAY TO DISCUSS YOUR APPLICATION!



HKC67 Technical Data Sheet

Double Coated Tape

General Purpose Permanent Double Coated Tape with a Polyester Carrier and White BOPP Release Liner

Product Features

- Excellent General Purpose Bag Enclosure Tape
- Bonds Plastic Courier and Mailer Envelopes
- Designed to Tear Films Up To 3Mils (75Microns) Thick
- *Weights approximate due to variations in raw materials/packaging

Release Liner	Overall Liner Widths Available	Adhesive Width Liner Side	Adhesive Width Exposed Side
1.8mil (45u) White Polypropylene (BOPP) Film	1/2" (12mm)	1/4" (6mm)	1/2" (12mm)
Adhesive	3/4" (19mm)	1/2" (12mm)	3/4" (19mm)
Rubber Based Adhesive	1" (25mm)	3/4" (19mm)	1" (25mm)
Liner Side Adhesion *	Available Widths	Adhesive Thickness	Adhesive Thickness
92 oz./in	1/2" (12mm)	1.6mils	1.0mils
Exposed Side Adhesion *	3/4" (19mm)	1.6mils	1.0mils
71 oz./in	1" (25mm)	1.6mils	1.0mils
Carrier	Diameter	*Weight	*Weight per Case
0.48 mil (12u) Clear Polyester	1/2" (12mm) - 16	3#/roll (1.0Kg)	39# (18.0 Kg)
	3/4" (19mm) - 16	5#/roll (2.0Kg)	42# (19.0 Kg)
	1" (25mm) - 16	6#/roll (3.0Kg)	44# (20.0Kg)
	Flat Rolls Per Case	Spools Per Case	Cases per Skid (Cases / Spools)
	1/2" x 3,000' (915m) - 12	1/2" x 21,000' (6,400m) - 1 *Weight: 23#/Spool/Case	24 / 45
	3/4" x 3,000' (915m) - 8	3/4" x 15,000' (4,572m) - 1 *Weight: 25#/Spool/Case	24 / 45
	1" x 3,000' (915m) - 6	1" x 12,000' (3,658m) - 1 *Weight: 25#/Spool/Case	24 / 45

* Above Reflect Typical Values

Notes:

- Low Slip Or No Slip Films Are Highly Recommended
- Corona Treatment On Film Surfaces Improves Adhesion Properties
- Adhesives Are Compliant With FDA Regulations For Indirect Food Contact - CFR 175.105
- Recommended Storage Conditions: 60-80 °F at 40-60% RH
- Ideal product application temperature range is 70°F to 100°F (21°C to 38°C). Initial application to surfaces at temperatures below 50°F (10°C) is not recommended

Fitness for Use in any end application is the sole responsibility of the user. Infinity Tapes makes no additional claims or warranties for suitability or fitness for use beyond those stated in our standard Terms & Conditions.