



HKC72

HIGH/LOW BAG SEALING SOLUTIONS

REQUEST A
SAMPLE TODAY!

Double Coated Tape

- Resealable adhesive on one side and permanent adhesive on the other
- True dry edge (TDE) technology
- Available with an extra wide finger lift edge
- Clear, custom printed HDPE release liner, "Remove Liner to Expose Adhesive" in red

Technical Info

- 1.2 mil (30 microns) high density polyethylene (HDPE) film
- Acrylic adhesive
- 8 oz./in liner side adhesion
- 13 oz./in exposed side adhesion
- 0.48 mil (12u) clear polyester carrier

Applications

- Polypropylene bags

Part Number	Item Description	Adhesive Technology	Application
HKC72	High/Low Double Coated Tape	Permanent/Resealable	Film Bags



Scan the code to request a sample or speak with our knowledgeable sales team.

CONTACT OUR TAPE EXPERTS TODAY TO DISCUSS YOUR APPLICATION!



HKC72 Technical Data Sheet

Double Coated Tape

A Double Coated (High/Low) Tape with Resealable Adhesive on One Side and a Permanent Adhesive on the Other. Supported with a Polyester Carrier and Clear Printed HDPE Release Liner

Product Features

- Tape Available with the Adhesive Shifted All the Way to the Right Side or Left Side of the Tape Providing an Extra Wide Finger Lift Edge
- Liner is a Clear HDPE Film Printed with the Words "Remove Liner To Expose Adhesive" in Red.
- HDPE Liner is Designed For Use On Polypropylene Bags
- TDE (True Dry Edge) Construction

Release Liner	Available Widths	Adhesive Width Liner Side	Adhesive Width Exposed Side
1.2mil (30 microns) High Density Polyethylene (HDPE) Film	5/8" (15mm)	15/64" (6mm)	11/64" (4.2mm)
Adhesive	Available Widths	Adhesive Thickness	Adhesive Thickness
Acrylic Adhesive	5/8" (15mm)	1.2mils	0.4mils
Liner Side Adhesion *	Diameter	Weight	Weight per Case
8.0 oz./in	5/8" (15mm) - 13	3#/roll (1Kg)	32# (14Kg)
Exposed Side Adhesion *	Flat Rolls Per Case	Spools Per Case	Cases per Skid (Cases / Spools)
13.0 oz./in	5/8" x 3,280' (1,000m) - 10	5/8" x 32,800' (10,000m) - 2	30 / 60
Carrier			
0.48 mil (12u) Clear Polyester			

Fitness for Use in any end application is the sole responsibility of the user. Infinity Tapes makes no additional claims or warranties for suitability or fitness for use beyond those stated in our standard Terms & Conditions.

* Above Reflect Typical Values

Notes:

- Low Slip or No Slip Films are Highly Recommended
- Corona Treatment on Film Surfaces Improves Adhesion Properties
- Recommended Storage Conditions: 60-80 °F at 40-60% RH
- Ideal product application temperature range is 70°F to 100°F (21°C to 38°C). Initial application to surfaces at temperatures below 50°F (10°C) is not recommended