



HKC91

RESEALABLE ADHESIVE FOR
TRANSIT APPLICATIONS

REQUEST A
SAMPLE TODAY!

Double Coated Tape

- Resealable adhesive on one side and an aggressive permanent adhesive on the other
- Smooth release from film surfaces
- Available in true dry edge (TDE) construction/lift edge on either side
- Clear, printed release liner available

Technical Info

- 1.8 mil (45 u) white polypropylene (BOPP) film
- Rubber-based hot melt adhesive
- 21 oz./in liner side adhesion
- 71 oz./in exposed side adhesion
- 0.48 mil (12u) clear polyester carrier

Applications

- Paper mailers and envelopes
- Plastic mailers and envelopes
- Low-energy substrate mailers and envelopes

Part Number	Item Description	Adhesive Technology	Application
HKC91	High/Low Double Coated Tape	Permanent/Resealable	Transit Envelopes



Scan the code to request a sample or speak with our knowledgeable sales team.

CONTACT OUR TAPE
EXPERTS TODAY TO DISCUSS
YOUR APPLICATION!



Infinity Tapes infinite possibilities

HKC91 Technical Data Sheet

Double Coated Tape

A Double Coated (High/Low) Tape with a resealable adhesive on one side and an aggressive permanent adhesive on the other. Supported with polyester carrier with a White BOPP release liner

Product Features

- Excellent Resealable Adhesive System With Easy Smooth Release From Film Surfaces
- Centered Adhesive Provides A Finger Lift Edge From Either Side Of The Tape
- Available in TDE (True Dry Edge) Construction
- Clear, Printed Release Liner Available

Release Liner	Overall Liner Widths Available	Adhesive Width Liner Side	Adhesive Width Exposed Side
1.8mil (45u) White Polypropylene (BOPP) Film	1/2"(12mm)	1/4" (6mm)	1/2" (12mm)
Adhesive	3/4" (19mm)	1/2" (12mm)	3/4" (19mm)
Rubber Based Hot Melt Adhesive	1" (25mm)	3/4" (19mm)	1" (25mm)
Liner Side Adhesion *	Available Widths	Adhesive Thickness	Adhesive Thickness
21 oz./in	1/2"(12mm)	1.5mils	1.0mils
Exposed Side Adhesion *	3/4" (19mm)	1.5mils	1.0mils
71 oz./in	1" (25mm)	1.5mils	1.0mils
Carrier	Diameter	Weight	Weight per Case
0.48 mil (12u) Clear Polyester	1/2"(12mm) - 16	3.0#/roll (1.0Kg)	37# (16.7Kg)
* Above Reflect Typical Values	3/4" (19mm) - 16	6.5#/roll (2.0Kg)	53# (24.1Kg)
	1" (25mm) - 16	9.0#/roll (4.0Kg)	55# (25.0Kg)
	Flat Rolls Per Case	Spools Per Case	Cases per Skid (Cases / Spools)
	1/2" x 3,000' (915m) - 12	1/2" x 21,000' (6,400m) - 1	24 / 45
	3/4" x 3,000' (915m) - 8	3/4" x 15,000' (4,572m) - 1	24 / 45
	1" x 3,000' (915m) - 6	1" x 12,000' (3,658m) - 1	24 / 45

Notes:

- Low Slip Or No Slip Films Are Highly Recommended
- Corona Treatment On Film Surfaces Improves Adhesion Properties
- Adhesives Are Compliant With FDA Regulations For Indirect Food Contact - CFR 175.105
- Recommended Storage Conditions: 60-80 °F at 40-60% RH
- Ideal product application temperature range is 70°F to 100°F (21°C to 38°C). Initial application to surfaces at temperatures below 50°F (10°C) is not recommended

Fitness for Use in any end application is the sole responsibility of the user. Infinity Tapes makes no additional claims or warranties for suitability or fitness for use beyond those stated in our standard Terms & Conditions.