



PP701.2

METALIZED RELEASE LINER SOLUTIONS

REQUEST A SAMPLE TODAY!

Release Liner

- Easy release silicone provides a smooth release
- Compatible with a wide variety of adhesives
- Metalized base film provides antistatic properties

Technical Info

- 1.18 mil metalized polypropylene film
- Coated on one side with easy release silicone
- Spooling (¼" to 1")
- Custom flexographic printing
- Diverse range of release values
- Multitude of coating chemistries

Applications

- Labels
- Graphic Films
- Tapes
- Hygiene
- Medical
- Industrial (Electronics, Building & Construction, Composites)
- Envelopes
- Food & Bakery

Part Number	Item Description	Liner Technology	Application
PP701.2	Metalized PP Release Liner	Polypropylene	Film & Paper Substrates



Scan the code to request a sample or speak with our knowledgeable sales team.

CONTACT OUR RELEASE LINER EXPERTS TODAY TO DISCUSS YOUR APPLICATION!



PP701.2 Technical Data Sheet

Release Liners

Polypropylene Release Liner 1.18 mil Metalized Polypropylene (PP) Film Coated on One Side with Our Easy Release Silicone Coating

Product Features

- Provides Smooth Release
- Compatible with wWide Variety of Adhesives
- Metalized Base Film Provides Antistatic Properties Which Will Eliminate the Inherent Static Cling Properties Typcial of Most Plastic Films.

Physical Properties	Target Range	Test Method
Release Values	20 - 40 gms/in	QA-11 ¹
Film Caliper ²	1.18mils +/-5%	Continuous measurement and/or micrometer measurements
Tensile Strength Break		
MD ²	24,600 psi	ASTM D-882
CD ²	40,500 psi	
Elongation at Break		
MD ²	160%	ASTM D-882
CD ²	60%	
	Available Widths	Available Lengths
	1/2" to 48"	Flat Rolls: Up to 16,400'

1. Procedure Utilizes Tesa 7475 Acrylic Based Adhesive Test. The Data Represents 7 Day Aging At 105°F. Test Results With Your Adhesive May Vary
2. These Values Are Based On Our Vendor's Raw Material Specifications

Notes:

- Recommended Storage Conditions: 60-80 °F at 40-60% RH
- Ideal product application temperature range is 70°F to 100°F (21°C to 38°C). Initial application to surfaces at temperatures below 50°F (10°C) is not recommended
- Fitness for Use in any end application is the sole responsibility of the user. Infinity Tapes makes no additional claims or warranties for suitability or fitness for use beyond those stated in our standard Terms & Conditions.