



# PT771

## INNOVATIVE TRANSFER TAPE SOLUTIONS

REQUEST A  
SAMPLE TODAY!

### Transfer Tape

- Economical general purpose permanent aggressive adhesive
- Will tear or distort films up to 2-3 mils in thickness
- Liner is hot knife cuttable
- Ideally used for permanent sealing of thin paper and plastic materials

### Technical Info

- 1.42 mil tinted blue polyester film release liner
- Rubber-based hot melt adhesive
- 95 oz./in adhesion

### Applications

- Paper bags
- Paper envelopes
- Plastic bags
- Plastic envelopes

Part Number	Item Description	Adhesive Technology	Application
PT771	PET Transfer Tape	Permanent	Transit Mailers



Scan the code to request a sample or speak with our knowledgeable sales team.

CONTACT OUR TAPE EXPERTS TODAY TO DISCUSS YOUR APPLICATION!



## PT771 Technical Data Sheet

## Transfer Tape

Economical General Purpose Permanent Unsupported Adhesive Transfer Tape with Tinted Blue Polyester Release Liner

### Product Features

- Aggressive Adhesive Tape for Permanent Sealing of Thin Paper and Plastic Bags and/or Envelopes
- Will Tear or Distort Films Up to 2-3 Mils in Thickness
- Liner is Hot Knife Cuttable

	Overall Liner Widths Available	Adhesive Width Liner Side	Adhesive Thickness
<b>Release Liner</b>	1/2" (12mm)	5/16" (8mm)	1.0 mil
<b>1.42 mil Polyester Film Tinted Blue</b>	3/4" (19mm)	1/2" (12mm)	1.0 mil
<b>Adhesive</b>	1" (25mm)	3/4" (19mm)	1.0 mil
<b>Rubber Based Hot Melt Adhesive</b>	<b>Diameter</b>	<b>Weight</b>	<b>Weight per Case</b>
<b>Adhesion *</b>	1/2"(12mm) - 12	2.0#/roll (0.9Kg)	25# (11.4Kg)
<b>95 oz./in</b>	3/4" (19mm) - 12	3.0#/roll (1.3Kg)	25# (11.4Kg)
	1" (25mm) - 12	4.0#/roll (1.8Kg)	25# (11.4Kg)
	<b>Flat Rolls Per Case</b>	<b>Cases per Skid</b>	
	1/2" x 3,000' (914m) - 12	24	
	3/4" x 3,000' (914m) - 8	24	
	1' x 3,000' (914m) - 6	24	

\* Above Reflect Typical Values

### Notes:

- Low Slip Or No Slip Films Are Highly Recommended
- Corona Treatment On Film Surfaces Improves Adhesion Properties
- Adhesives Are Compliant With FDA Regulations For Indirect Food Contact - CFR 175.105
- Recommended Storage Conditions: 60-80 °F at 40-60% RH
- Ideal product application temperature range is 70°F to 100°F (21°C to 38°C). Initial application to surfaces at temperatures below 50°F (10°C) is not recommended

Fitness for Use in any end application is the sole responsibility of the user. Infinity Tapes makes no additional claims or warranties for suitability or fitness for use beyond those stated in our standard Terms & Conditions.