



# PT774

HIGH PERFORMANCE  
TRANSFER TAPE SOLUTIONS

REQUEST A  
SAMPLE TODAY!

## Transfer Tape

- High performance permanent adhesive
- Superior bonding properties
- Will tear or distort films greater than 3 mils in thickness
- Liner is hot knife cuttable

## Technical Info

- 1.42 mil tinted blue polyester film release liner
- Rubber-based hot melt adhesive
- 143 oz./in adhesion

## Applications

- Heavy walled plastic bags
- Envelopes
- Corrugated boxes
- Card stock

Part Number	Item Description	Adhesive Technology	Application
PT774	PET Transfer Tape	Permanent	Transit Packaging



Scan the code to request a sample or speak with our knowledgeable sales team.

CONTACT OUR TAPE EXPERTS TODAY TO DISCUSS YOUR APPLICATION!



**PT774 Technical Data Sheet**

**Transfer Tape**

High Performance Permanent  
Unsupported Adhesive Transfer Tape with  
Tinted Blue Polyester Release Liner

**Product Features**

- More Aggressive Than PT777 Having Superior Bonding Properties for Heavier Walled Plastic Bags, Envelopes and Some Corrugated Boxes and Card Stock
- Will Tear or Distort Films >3 Mils in Thickness
- Liner is Hot Knife Cuttable

	Overall Liner Widths Available	Adhesive Width Liner Side	Adhesive Thickness
<b>Release Liner</b>	1/2" (12mm)	5/16" (8mm)	4.0 mil
<b>1.42 mil Polyester Film Tinted Blue</b>	3/4" (19mm)	1/2" (12mm)	4.0 mil
<b>Adhesive</b>	1" (25mm)	3/4" (19mm)	4.0 mil
<b>Rubber Based Hot Melt Adhesive</b>	<b>Diameter</b>	<b>Weight</b>	<b>Weight per Case</b>
<b>Adhesion *</b>	1/2"(12mm) - 15	3.0#/roll (1.4Kg)	37#(16.8Kg)
<b>143 oz./in</b>	3/4" (19mm) - 15	4.5#/roll (2.0Kg)	37#(16.8Kg)
	1" (25mm) - 15	6.0#/roll (2.7Kg)	37#(16.8Kg)
	<b>Flat Rolls Per Case</b>	<b>Cases per Skid</b>	
	1/2" x 3,000' (914m) - 12	24	
	3/4" x 3,000' (914m) - 8	24	
	1' x 3,000' (914m) - 6	24	

\* Above Reflect Typical Values

**Notes:**

- Low Slip Or No Slip Films Are Highly Recommended
- Corona Treatment On Film Surfaces Improves Adhesion Properties
- Adhesives Are Compliant With FDA Regulations For Indirect Food Contact - CFR 175.105
- Recommended Storage Conditions: 60-80 °F at 40-60% RH
- Ideal product application temperature range is 70°F to 100°F (21°C to 38°C). Initial application to surfaces at temperatures below 50°F (10°C) is not recommended

Fitness for Use in any end application is the sole responsibility of the user. Infinity Tapes makes no additional claims or warranties for suitability or fitness for use beyond those stated in our standard Terms & Conditions.