



# T671

## ECONOMICAL GENERAL PURPOSE TRANSFER TAPE

REQUEST A SAMPLE TODAY!

### Transfer Tape

- Economical general purpose adhesive system
- High tack and bond adhesive system
- Paper liner is available standard printed red with the words, "Remove Liner to Expose Adhesive"
- Custom printing and colors are available

### Technical Info

- 42# Printed red SCK paper
- Permanent unsupported rubber-based hot melt adhesive
- 95 oz./in adhesion
- Spooling (¼" to 1")
- Custom flexographic printing
- Diverse range of release values
- Multitude of coating chemistries

### Applications

- Thin paper bags
- Thin paper envelopes
- Plastic bags
- Plastic envelopes

Part Number	Item Description	Adhesive Technology	Application
T671	Permanent Transfer Tape	Permanent	Film & Paper Mailers



Scan the code to request a sample or speak with our knowledgeable sales team.

CONTACT OUR TAPE EXPERTS TODAY TO DISCUSS YOUR APPLICATION!



## T671 Technical Data Sheet

## Transfer Tape

Economical General Purpose Permanent Unsupported Adhesive Transfer Tape with a Paper Release Liner

### Product Features

- Aggressive Adhesive Tape for Permanent Sealing of Thin Paper and Plastic Bags and/or Envelopes
- Good General Purpose Bonding Properties
- Paper Liner is Available Standard Printed Red with the Words "Remove Liner To Expose Adhesive". Custom Printing and Colors are also Available.

	Overall Liner Widths Available	Adhesive Width Liner Side	Adhesive Thickness
<b>Release Liner</b>	1/2" (12mm)	5/16" (8mm)	1.0 mil
<b>42# Printed Red SCK Paper</b>	3/4" (19mm)	1/2" (12mm)	1.0 mil
<b>Adhesive</b>	1" (25mm)	1/2" (12mm)	1.0 mil
<b>Rubber Based Hot Melt Adhesive</b>	1" (25mm)	3/4" (19mm)	1.0 mil
Adhesion *	Diameter	Weight	Weight per Case
95 oz./in	1/2"(12mm) - 13	2#/roll (0.9Kg)	25# (11.3Kg)
	3/4" (19mm) - 13	3.75#/roll (1.7Kg)	31# (14.1Kg)
	1" (25mm) - 13	5#/roll (2.2Kg)	31# (14.1Kg)
	Flat Rolls Per Case	Cases per Skid	
	1/2" x 3,000' (914m) - 10	24	
	3/4" x 3,000' (914m) - 7	24	
	1' x 3,000' (914m) - 5	24	

\* Above Reflect Typical Values

### Notes:

- Low Slip Or No Slip Films Are Highly Recommended
- Corona Treatment On Film Surfaces Improves Adhesion Properties
- Adhesives Are Compliant With FDA Regulations For Indirect Food Contact - CFR 175.105
- Recommended Storage Conditions: 60-80 °F at 40-60% RH
- Ideal product application temperature range is 70°F to 100°F (21°C to 38°C). Initial application to surfaces at temperatures below 50°F (10°C) is not recommended

Fitness for Use in any end application is the sole responsibility of the user. Infinity Tapes makes no additional claims or warranties for suitability or fitness for use beyond those stated in our standard Terms & Conditions.