



T678

PERMANENT TRANSFER TAPE SOLUTIONS

REQUEST A
SAMPLE TODAY!

Transfer Tape

- General purpose permanent adhesive system
- High tack and bonding properties
- Paper liner is available standard printed red with the words, "Remove Liner to Expose Adhesive"
- Custom printing and colors are available

Technical Info

- 42# Printed red SCK paper
- Permanent unsupported rubber-based hot melt adhesive
- 108 oz./in adhesion
- Spooling (¼" to 1")
- Custom flexographic printing
- Diverse range of release values
- Multitude of coating chemistries

Applications

- Poly bags
- Envelopes
- Corrugated boxes
- Card stock

Part Number	Item Description	Adhesive Technology	Application
T678	Permanent Transfer Tape	Rubber-Based Hot Melt	Transit Packages



Scan the code to request a sample or speak with our knowledgeable sales team.

CONTACT OUR TAPE EXPERTS TODAY TO DISCUSS YOUR APPLICATION!



T678 Technical Data Sheet

Transfer Tape

General Purpose Permanent Unsupported Adhesive Transfer Tape with a Paper Release Liner

Product Features

- More Aggressive than T671 Having Good Overall Bonding Properties for Sealing Poly Bags, Envelopes and Some Corrugated Boxes and Card Stock
- Paper Liner is Available Standard Printed Red with the Words "Remove Liner To Expose Adhesive". Custom Printing and Colors are also Available.

	Overall Liner Widths Available	Adhesive Width Liner Side	Adhesive Thickness
Release Liner	1/2" (12mm)	5/16" (8mm)	1.5 mil
42# Printed Red SCK Paper	3/4" (19mm)	1/2" (12mm)	1.5 mil
Adhesive	1" (25mm)	1/2" (12mm)	1.5 mil
Rubber Based Hot Melt Adhesive	1" (25mm)	3/4" (19mm)	1.5 mil
Adhesion *	Diameter	Weight	Weight per Case
108 oz./in	1/2" (12mm) - 17	4#/roll (1.8Kg)	49# (22.3Kg)
	3/4" (19mm) - 17	7#/roll (3.1Kg)	57# (25.8Kg)
	1" (25mm) - 17	9#/roll (4.0Kg)	55# (25.0Kg)
Flat Rolls Per Case		Cases per Skid	
1/2" x 3,000' (914m) - 12		24	
3/4" x 3,000' (914m) - 8		24	
1' x 3,000' (914m) - 6		24	

* Above Reflect Typical Values

Notes:

- Low Slip Or No Slip Films Are Highly Recommended
- Corona Treatment On Film Surfaces Improves Adhesion Properties
- Adhesives Are Compliant With FDA Regulations For Indirect Food Contact - CFR 175.105
- Recommended Storage Conditions: 60-80 °F at 40-60% RH
- Ideal product application temperature range is 70°F to 100°F (21°C to 38°C). Initial application to surfaces at temperatures below 50°F (10°C) is not recommended

Fitness for Use in any end application is the sole responsibility of the user. Infinity Tapes makes no additional claims or warranties for suitability or fitness for use beyond those stated in our standard Terms & Conditions.