



T680

RESEALABLE TRANSFER TAPE SOLUTIONS

REQUEST A
SAMPLE TODAY!

Transfer Tape

- Excellent resealable adhesive system
- Easy smooth release properties
- Paper liner is available standard printed red with the words, "Remove Liner to Expose Adhesive"
- Custom printing and colors are available

Technical Info

- 42# Printed blue SCK paper
- Resealable unsupported rubber-based hot melt adhesive
- 7 oz./in adhesion
- Spooling (¼" to 1")
- Custom flexographic printing
- Diverse range of release values
- Multitude of coating chemistries

Applications

- Film
- Paper

Part Number	Item Description	Adhesive Technology	Application
T680	Resealable Transfer Tape	Resealable	Film & Paper Surfaces



Scan the code to request a sample or speak with our knowledgeable sales team.

CONTACT OUR TAPE EXPERTS TODAY TO DISCUSS YOUR APPLICATION!



T680 Technical Data Sheet

Transfer Tape

Unsupported Resealable Adhesive
Transfer Tape with a Paper Release Liner

Product Features

- Excellent Resealable Adhesive System with Easy Smooth Release from Film and Paper Surfaces
- Paper Liner is Available Standard Printed Red with the Words "Remove Liner To Expose Adhesive". Custom Printing and Colors are also Available.

	Overall Liner Widths Available	Adhesive Width Liner Side	Adhesive Thickness
Release Liner	1/2" (12mm)	5/16" (8mm)	1.5 mil
42# Printed Blue SCK Paper	3/4" (19mm)	1/2" (12mm)	1.5 mil
Adhesive	1" (25mm)	3/4" (19mm)	1.5 mil
Rubber Based Hot Melt Adhesive	Diameter	Weight	Weight per Case
Adhesion *	1/2"(12mm) - 13	2.0#/roll (0.9Kg)	25# (11.4Kg)
7 oz./in	3/4" (19mm) - 13	3.0#/roll (3.1Kg)	25# (11.4Kg)
	1" (25mm) - 13	4.5#/roll (2.0Kg)	28# (12.7Kg)
	Flat Rolls Per Case	Cases per Skid	
	1/2" x 3,000' (914m) - 12	24	
	3/4" x 3,000' (914m) - 8	24	
	1' x 3,000' (914m) - 6	24	

* Above Reflect Typical Values

Notes:

- Low Slip Or No Slip Films Are Highly Recommended
- Corona Treatment On Film Surfaces Improves Adhesion Properties
- Adhesives Are Compliant With FDA Regulations For Indirect Food Contact - CFR 175.105
- Recommended Storage Conditions: 60-80 °F at 40-60% RH
- Ideal product application temperature range is 70°F to 100°F (21°C to 38°C). Initial application to surfaces at temperatures below 50°F (10°C) is not recommended

Fitness for Use in any end application is the sole responsibility of the user. Infinity Tapes makes no additional claims or warranties for suitability or fitness for use beyond those stated in our standard Terms & Conditions.